

L488 - DMX Protocol

Revision: A Valid from firmware version: 1.0 DMX mode Default DMX DMX value Name **DMX** percentage Function Value Standard (14ch) Simplified (8ch) 31 0.0% 12.2% Closed 32 63 12.5% 24 7% Open 64 127 25.1% 49.8% Synchronous strobe from slow to fast Strobe/Shutter 0(0%) 1 1 128 159 50.2% 62.4% Open 160 223 62.7% 87.5% Random strobe from slow to fast 224 255 87.8% 100.0% Open 2 2 Intensity 0 255 0.0% 100.0% No light → Full light 0(0%) 3 3 Red 1 0 255 0.0% 100.0% No light → Full red 1 0(0%) 4 3 Red 2 0 255 0.0% 100.0% No light → Full red 2 0(0%) 4 0 100.0% 0(0%) 5 Green 1 255 0.0% No light → Full green 1 0 0.0% 100.0% 6 4 Green 2 255 No light → Full green 2 0(0%) 5 Blue 1 0 255 0.0% 100.0% 0(0%) No light → Full blue 1 Blue 2 8 5 0 255 0.0% 100.0% 0(0%) No light → Full blue 2 White 1 6 0 255 0.0% 100.0% No light → Full white 1 0(0%) 0 10 255 0.0% 100.0% 0(0%) 6 White 2 No light → Full white 2 11 7 Amber 1 0 255 0.0% 100.0% No light → Full amber 1 0(0%) 12 7 Amber 2 0 255 0.0% 100.0% No light → Full amber 2 0(0%) 0 24 0.0% 9.4% No function 25 35 9.8% 13.7% 3200K 36 46 14.1% 18.0% 3400K 47 57 18.4% 22.4% 3600K 58 68 22 7% 26.7% 3800K 79 27.1% 69 31.0% 4000K 80 90 31.4% 35.3% 4200K 91 101 35.7% 39.6% 4400K 102 112 40.0% 43.9% 4600K 113 123 44.3% 48.2% 4800K 5000K 124 134 48.6% 52 5% 13 8 0(0%) Color temperature 1 135 145 52.9% 56.9% 5200K 5400K 146 156 57.3% 61 2% 157 167 61.6% 65.5% 5600K 168 178 65.9% 69.8% 5800K 179 189 70.2% 74.1% 6000K 190 200 74.5% 78.4% 6200K 201 211 78.8% 82.7% 6400K 212 222 83.1% 87.1% 6600K 223 233 87 5% 91.4% 6800K 234 244 91.8% 95.7% 7000K 245 255 96.1% 100.0% 7200K 0 24 0.0% 9.4% No function 25 35 3200K 9.8% 13.7% 36 46 14.1% 18.0% 3400K 47 57 3600K 18.4% 22.4% 58 68 22.7% 26.7% 3800K 27.1% 4000K 69 79 31.0% 80 90 31.4% 35.3% 4200K 91 101 35.7% 39.6% 4400K 102 112 40.0% 43.9% 4600K 113 123 44.3% 48.2% 4800K 124 134 48.6% 52.5% 5000K 14 Color temperature 2 0(0%) 135 145 52.9% 56.9% 5200K 146 156 57.3% 61 2% 5400K 61.6% 65.5% 5600K 157 167 168 178 65.9% 69.8% 5800K 179 189 70.2% 74.1% 6000K 200 74 5% 78 4% 6200K 190 201 211 78.8% 82.7% 6400K 6600K 212 222 83.1% 87.1% 223 233 87.5% 91.4% 6800K 234 244 91.8% 95.7% 7000K 245 255 96.1% 100.0% 7200K