

## L654PII - DMX Protocol

Revision: B Valid from firmware version: 1.1							
Basic (9ch)	Name	DN	DMX value		ercentage	Function	Default DMX Value
		0	31	0.0%	12.2%	Closed	
		32	63	12.5%	24.7%	Open	
1	Strobe/Shutter	64	127	25.1%	49.8%	Synchronous strobe from slow to fast	0(0%)
	on obe, on and	128	159	50.2%	62.4%	Open	0(070)
		160	223	62.7%	87.5%	Random strobe from slow to fast	
		224	255	87.8%	100.0%	Open	
2	Intensity	0	255	0.0%	100.0%	No light → Full light	0(0%)
		0	65535	0.0%	100.0%	Intensity fade, fine (LSB)	((,,,,
3	Red	0	255	0.0%	100.0%	No light → Full light	0(0%)
		0	65535	0.0%	100.0%	Intensity fade, fine (LSB)	- ()
4	Green	0	255	0.0%	100.0%	No light → Full light	0(0%)
		0	65535	0.0%	100.0%	Intensity fade, fine (LSB)	-(-,-)
5	Blue	0	255	0.0%	100.0%	No light → Full light	0(0%)
	<u> </u>	0	65535	0.0%	100.0%	Intensity fade, fine (LSB)	0(070)
		0	9	0.0%	3.5%	No function	
6		10	39	3.9%	15.3%	Rainbow scene 1	
		40	71	15.7%	27.8%	Rainbow scene 2	
	Rainbow Function	72	103	28.2%	40.4%	Rainbow scene 3	0(0%)
		104	135	40.8%	52.9%	Rainbow scene 4	
		136	167	53.3%	65.5%	Rainbow scene 5	
		168	199	65.9%	78.0%	Rainbow scene 6	
		200	231	78.4%	90.6%	Rainbow scene 7	
		232	255	91.0%	100.0%	Rainbow flow from slow to fast	
7		0	24	0.0%	9.4%	No function	
		25	35	9.8%	13.7%	3200K	
		36	46	14.1%	18.0%	3400K	
		47	57	18.4%	22.4%	3600K	
		58	68	22.7%	26.7%	3800K	
		69	79	27.1%	31.0%	4000K	
	Color temperature	80	90	31.4%	35.3%	4200K	0(0%)
		91	101	35.7%	39.6%	4400K	
		102	112	40.0%	43.9%	4600K	
		113	123	44.3%	48.2%	4800K 4800K	
		124	134	48.6%	52.5%	5000K	
		135	145	52.9%	56.9%	5200K	
		146	156	57.3%	61.2%	5400K	
		157	167	61.6%	65.5%	5600K	
		168	178	65.9%	69.8%	5800K	
		179	189	70.2%	74.1%	6000K	
		190	200	74.5%	78.4%	6200K	
		201	211	78.8%	82.7%	6400K	
		212	222	83.1%	87.1%	6600K	
		223	233	87.5%	91.4%	6800K	
		234	244	91.8%	95.7%	7000K	
		245	255	96.1%	100.0%	7200K	
		0	55	0.0%	21.6%	No function	
		56	105	22.0%	41.2%	Build_in Program 1	
	Build_in Program	106	155	41.6%	60.8%	Build_in Program 2	0(0%)
		156	205	61.2%	80.4%	Build_in Program 3	
		206	255	80.8%	100.0%	Build_in Program 4	
8		0	55	0.0%	21.6%	No function	
	Build_in Program	56	105	22.0%	41.2%	Build_in Program 1	
		106	155	41.6%	60.8%	Build_in Program 2	0(0%)
	_	156	205	61.2%	80.4%	Build_in Program 3	` '
		206	255	80.8%	100.0%	Build_in Program 4	
		0	55	0.0%	21.6%	No function	
9		56	105	22.0%	41.2%	Build_in Program 1	0(0%)
	Build_in Program						
a		106	155	41.6%	60.8%	Build_in Program 2	0(0%)
9	regram	156	205	61.2%	80.4%	Build_in Program 3	