

1500 II Wash - DMX Protocol

Revision: A

Valid from firmware version: 5.0

DMX mode			Name	DMX value		DMX percentage		Function	Default DMX Value
Standard (17ch)	Simplified (16ch)	Extended (22ch)							
1	1	1	Strobe/Shutter	0	31	0.0%	12.2%	Closed	0(0%)
				32	63	12.5%	24.7%	Open	
				64	127	25.1%	49.8%	Synchronous strobe from slow to fast	
				128	159	50.2%	62.4%	Open	
				160	223	62.7%	87.5%	Random strobe from slow to fast	
				224	255	87.8%	100.0%	Open	
2	2	2	Intensity	0	255	0.0%	100.0%	No light → Full light	0(0%)
3	3	0		65535	0.0%	100.0%	Intensity fade, fine (LSB)		
4	3	4	Cyan	0	255	0.0%	100.0%	White → Full cyan	0(0%)
	5	0		65535	0.0%	100.0%	Cyan fade, fine (LSB)		
5	4	6	Magenta	0	255	0.0%	100.0%	White → Full magenta	0(0%)
	7	0		65535	0.0%	100.0%	Magenta fade, fine (LSB)		
6	5	8	Yellow	0	255	0.0%	100.0%	White → Full yellow	0(0%)
	9	0		65535	0.0%	100.0%	Yellow fade, fine (LSB)		
7	6	10	CMY color macro	0	15	0.0%	5.9%	CMY color macro off	0(0%)
		16		135	6.3%	52.9%	CMY synchronous color from slow to fast		
		136		255	53.3%	100.0%	CMY random color from slow to fast		
8	7	11	CTO	0	255	0.0%	100.0%	Warm → Cold	0(0%)
		12		0	65535	0.0%	100.0%	CTO fade, fine (LSB)	
9	8	13	Color wheel 1	0	15	0.0%	5.9%	Open	0(0%)
				16	31	6.3%	12.2%	Color 1	
				32	47	12.5%	18.4%	Color 2	
				48	63	18.8%	24.7%	Color 3	
				64	79	25.1%	31.0%	Color 4	
				80	95	31.4%	37.3%	Color 5	
				96	111	37.6%	43.5%	Color 6	
				112	127	43.9%	49.8%	Color 7	
				128	187	50.2%	73.3%	Color continous rotation CW from slow to fast	
				188	195	73.7%	76.5%	Stop	
				196	255	76.9%	100.0%	Color continous rotation CCW from slow to fast	
10	9	14	Color wheel 2	0	15	0.0%	5.9%	Open	0(0%)
				16	31	6.3%	12.2%	Color 1	
				32	47	12.5%	18.4%	Color 2	
				48	63	18.8%	24.7%	Color 3	
				64	79	25.1%	31.0%	Color 4	
				80	95	31.4%	37.3%	Color 5	
				96	111	37.6%	43.5%	Color 6	
				112	127	43.9%	49.8%	Color 7	
				128	187	50.2%	73.3%	Color continous rotation CW from slow to fast	
				188	195	73.7%	76.5%	Stop	
				196	255	76.9%	100.0%	Color continous rotation CCW from slow to fast	
11	10	15	Frost/Zoom	0	29	0.0%	11.4%	White → Full frost	0(0%)
	16	30		255	11.8%	100.0%	Narrow → Wide		
		0	65535	0.0%	100.0%	Zoom, fine (LSB)			
12	11	17	Pan	0	255	0.0%	100.0%	Pan	0(0%)
13	12	18		0	65535	0.0%	100.0%	Pan, fine (LSB)	
14	13	19	Tilt	0	255	0.0%	100.0%	Tilt	46(18.0%)
15	14	20		0	65535	0.0%	100.0%	Tilt, fine (LSB)	
16	15	21	Scan speed	0	255	0.0%	100.0%	Scan speed from fast to slow	0(0%)
17	16	22	Special controls	0	9	0.0%	3.5%	No function	0(0%)
				10	19	3.9%	7.5%	Open light after 5 seconds	
				20	29	7.8%	11.4%	Close light after 5 seconds	
				30	39	11.8%	15.3%	Color wheel half color switch	
				40	49	15.7%	19.2%	Color wheel random positioning	
				50	59	19.6%	23.1%	Reserved	
				60	69	23.5%	27.1%	Reset all motor after 5 seconds	
				70	79	27.5%	31.0%	Scan motor reset after 5 seconds	
				80	89	31.4%	34.9%	All color motor reset after 5 seconds	
				90	99	35.3%	38.8%	Reserved	
				100	109	39.2%	42.7%	All strobe motor reset after 5 seconds	
				110	119	43.1%	46.7%	Other motor reset after 5 seconds	
				120	129	47.1%	50.6%	Built-in program 1	
				130	139	51.0%	54.5%	Built-in program 2	
				140	149	54.9%	58.4%	Built-in program 3	
				150	159	58.8%	62.4%	Built-in program 4	
				160	169	62.7%	66.3%	Built-in program 5	
				170	179	66.7%	70.2%	Built-in program 6	
				180	189	70.6%	74.1%	Built-in program 7	
				190	199	74.5%	78.0%	Built-in program 8	
200	209	78.4%	82.0%	Built-in program 9					
210	219	82.4%	85.9%	Built-in program 10					
220	255	86.3%	100.0%	Voice control					